Door trimming allowance



	ICE	Ε				
Internal	Maximum from top	Maximum from bottom	Maximum from each edge	* Overall width	* Overall height	
Oak Original Standard & Glazed	15mm	15mm	15mm	30mm	30mm	
Oak Essential Standard & Glazed	15mm	15mm	15mm	30mm	30mm	
Statement Oak	20mm	20mm	20mm	40mm	40mm	
Standard Oak Standard & Glazed	6mm	6mm	6mm	12mm	12mm	
White Primed Standard & Glazed	6mm	6mm	6mm	12mm	12mm	
Mode by XL Standard & Glazed	6mm	6mm	6mm	12mm	12mm	
Walnut Standard & Glazed	6mm	6mm	6mm	12mm	12mm	
White Moulded Standard & Glazed	6mm	6mm	6mm	12mm	12mm	
Pre-Finished White Standard & Glazed	6mm	6mm	6mm	12mm	12mm	
Pine Standard & Glazed	6mm	6mm	6mm	12mm	12mm	
ALL Fire Doors 🔥	2mm	2mm	2mm	4mm	4mm	
Bi-Folds	Not suitable for trimming from any edge					
	Maximum from top	Maximum from bottom	Maximum from non-rebated edges ONLY	Overall width	* Overall height	
Rebated Door Pairs Standard & Glazed	6mm	6mm	6mm	12mm	12mm	

	TRIMMING ALLOWANCE						
External	Maximum from top	Maximum from bottom	Maximum from each edge	* Overall width	* Overall height		
All External doors	12mm	12mm	12mm	24mm	24mm		
Arched Top Pine Gate	0mm	12.5mm	12.5mm	25mm	12.5mm		
Ledged & Braced Pine Gate and Ledged Pine Gate	12.5mm	12.5mm	12.5mm	25mm	25mm		

^{*}Any reduction must be removed evenly from each edge of the door: e.g. to trim your door by 8mm in width, remove 4mm off each side.